

DZOFILM

PAVO | ANAMORPHIC
2X

28 / 32 / 40 / 55 / 65 / 75 / 100 / 135 / 180 MM



Mount
PL / EF

Image Circle
SUPER 35

Focusing Distance
0.366m

Focal Length	28 mm	32 mm	40 mm	55 mm	65 mm
Colour	Space Grey + Black				
Flare Option	Neutral / Blue				
Mount	PL / EF				
Aperture	T2.1 - T22				T2.8 - T22
Image Circle	ø31.5mm (S35)				
Construction of Optics	15Elements in 13 Groups	15Elements in 13 Groups	15 Elements in 14 Groups	14 Elements in 13 Groups	17 Elements in 12 Groups
Flange Distance	52mm(PL) / 44mm(EF)				
Close Focus (from sensor plane)	0.4m / 1ft4in	0.4m / 1ft4in	0.45m / 1ft6in	0.6m / 2ft	0.366m / 1ft2.4in
Squeeze Factor	2X				
Iris Control	Manual (79°)	Manual (59°)	Manual (58°)	Manual (63°)	Manual (73°)
Focus Control	Manual (270°)				Manual (300°)
Front Dia.	ø95mm / 3.74"				
Length (from lens front to flange plane)	106.3mm / 4.19"	105.7mm / 4.16"	107.6mm / 4.24"	108.4mm / 4.26"	160mm / 6.3"
Iris Blade	16				
Filter Size	M86				
Gear Pitch	0.8 Mod				
Material	Aluminum Alloy				
Weight (Product)	≈1203g	≈1278g	≈1300g	≈1262g	≈1963g

Focal Length	75 mm	100 mm	135 mm	180 mm
Colour	Space Grey + Black			
Flare Option	Neutral / Blue			
Mount	PL / EF			
Aperture	T2.1 - T22	T2.4 - T22	T2.5 - T22	T2.8 - T22
Image Circle	ø31.5mm (S35)			
Construction of Optics	15 Elements in 14 Groups	14 Elements in 13 Groups	16 Elements in 11 Groups	16 Elements in 11 Groups
Flange Distance	52mm(PL) / 44mm(EF)			
Close Focus (from sensor plane)	0.84m / 2ft9in	0.95m / 3ft1in	0.99m / 3ft3in	1.04m / 3ft5in
Squeeze Factor	2X			
Iris Control	Manual (67°)	Manual (69°)	Manual (79°)	Manual (79°)
Focus Control	Manual (270°)			
Front Dia.	ø95mm / 3.74"			
Length (from lens front to flange plane)	126.9mm / 4.99"	143.1mm / 5.63"	160mm / 6.3"	160mm / 6.3"
Iris Blade	16			
Filter Size	M86			
Gear Pitch	0.8 Mod			
Material	Aluminum Alloy			
Weight (Product)	≈1466g	≈1654g	≈1994g	≈1950g